





特點 Features


- EUMAX歐巨重載連接器品質優良，產品綫齊全，性價比高
- 接插體電氣規格符合VDE 0110/0627規範，防護等級IP65
- 耐熱等級UL 94V-O，工作溫度範圍-40℃~125℃
- 冷壓連接不含冷壓針，請根據綫徑尺寸另行選購
- 提供高結構插頭/底座外殼和各種PG牙/公制牙入綫孔徑
- EUMAX provides cost-effective, high-quality Heavy Duty Connector product lines
- Conforms to VDE 0110/0627 and IP 65 protection class
- UL 94V-0 ratings, working temperature -40°C~125°C
- Crimp terminals should be ordered separately per wire cross section
- High construction hoods/housings and various PG/Metric sizes upon request




HA Series 16A/250V
HQ Series 16A/400V



HE Series 16A/400V



HD/HDD Series 10A/250V



HA/HE Series 16A/250V



HD/HDD Series 10A/250V




退針工具
Removal Tool

HA/HQ Series		3+ ⊕	4+ ⊕	5+ ⊕	10+ ⊕	16+ ⊕	32+ ⊕
螺絲連接 Screw Connection	公(M)	HA-003-M	HA-004-M	-	HA-010-M	HA-016-M	HA-032-M
	母(F)	HA-003-F	HA-004-F	-	HA-010-F	HA-016-F	HA-032-F
冷壓連接 Crimp Connection	公(M)	-	-	HQ-005-M	HA-010-MC	HA-016-MC	HA-032-MC
	母(F)	-	-	HQ-005-F	HA-010-FC	HA-016-FC	HA-032-FC
外殼 Housing Size		1	1	1	2	5	7

HE Series		6+ ⊕	10+ ⊕	16+ ⊕	24+ ⊕	32+ ⊕	48+ ⊕
螺絲連接 Screw Connection	公(M)	HE-006-M	HE-010-M	HE-016-M	HE-024-M	HE-032-M	HE-048-M
	母(F)	HE-006-F	HE-010-F	HE-016-F	HE-024-F	HE-032-F	HE-048-F
彈片連接 Spring Clamp	公(M)	HE-006-MS	HE-010-MS	HE-016-MS	HE-024-MS	HE-032-MS	HE-048-MS
	母(F)	HE-006-FS	HE-010-FS	HE-016-FS	HE-024-FS	HE-032-FS	HE-048-FS
冷壓連接 Crimp Connection	公(M)	HE-006-MC	HE-010-MC	HE-016-MC	HE-024-MC	HE-032-MC	HE-048-MC
	母(F)	HE-006-FC	HE-010-FC	HE-016-FC	HE-024-FC	HE-032-FC	HE-048-FC
外殼 Housing Size		3	4	6	8	10	12

HD Series		25+ ⊕	40+ ⊕	50+ ⊕	64+ ⊕	80+ ⊕	128+ ⊕
接插體 Inserts	公(M)	HD-025-M	HD-040-M	HD-050-M	HD-064-M	HD-080-M	HD-128-M
	母(F)	HD-025-F	HD-040-F	HD-050-F	HD-064-F	HD-080-F	HD-128-F
外殼 Housing Size		5	6	7	8	10	12

HDD Series		24+ ⊕	42+ ⊕	72+ ⊕	108+ ⊕	144+ ⊕	216+ ⊕
接插體 Inserts	公(M)	HDD-024-M	HDD-042-M	HDD-072-M	HDD-108-M	HDD-144-M	HDD-216-M
	母(F)	HDD-024-F	HDD-042-F	HDD-072-F	HDD-108-F	HDD-144-F	HDD-216-F
外殼 Housing Size		3	4	6	8	10	12

冷壓針 Crimp Terminal	綫徑mm ² Wire Cross Section	銀針 Silver Plated		金針 Gold Plated	
		HA/HE	HD/HDD	HA/HE	HD/HDD
公針 Pin 	0.5	CEM-0.5	CDM-0.5	DEM-0.5	DDM-0.5
	0.75	CEM-0.75	CDM-0.75	DEM-0.75	DDM-0.75
	1.0	CEM-1.0	CDM-1.0	DEM-1.0	DDM-1.0
	1.5	CEM-1.5	CDM-1.5	DEM-1.5	DDM-1.5
	2.5	CEM-2.5	CDM-2.5	DEM-2.5	DDM-2.5
母針 Socket 	0.5	CEF-0.5	CDF-0.5	DEF-0.5	DDF-0.5
	0.75	CEF-0.75	CDF-0.75	DEF-0.75	DDF-0.75
	1.0	CEF-1.0	CDF-1.0	DEF-1.0	DDF-1.0
	1.5	CEF-1.5	CDF-1.5	DEF-1.5	DDF-1.5
	2.5	CEF-2.5	CDF-2.5	DEF-2.5	DDF-2.5
HA/HE HD/HDD	4.0	CEM-4.0	-	DEM-4.0	-
	4.0	CEF-4.0	-	DEF-4.0	-

型號 P/N	Removal-AA	Removal-DD	Removal-EE	Removal-MM
冷壓針 Crimp Terminal	 CA/5A	 HD/HDD/10A	 HA/HE/16A	 CM/40A

HA/HB Series Hoods

HA/HB Series		插頭外殼 Hoods				底座外殼 Housings			
入線方式 Entry		側入線 Side Entry		上入線 Top Entry		底部入線 Bulkhead Mounted		側入線 Surface Mounted	
鎖定方式 Locking									
外殼規格	入線孔徑	單扣 1 Lever	雙扣 2 Levers	單扣 1 Lever	雙扣 2 Levers	單扣 1 Lever	雙扣 2 Levers	單扣 1 Lever	雙扣 2 Levers
Size 1	M20	H3A-MTS-M20	-	H3A-MTG-M20	-	H3A-MAG-MAGS	-	H3A-MAGSV-M20	-
Size 2	M20	H10A-TS-M20	-	H10A-TG-M20	-	H10A-AG	-	H10A-SGR-M20	-
Size 3	M20	H6B-TS-M20	-	H6B-TG-M20	-	H6B-AG	-	H6B-SGR-M20	-
Size 4	M25	H10B-TS-R0-M25	H10B-TS-M25	H10B-TG-R0-M25	H10B-TG-M25	H10B-AG-LB	H10B-AG	H10B-SGR-LB-M25	H10B-SGR-M25
Size 5	M25	H16A-TS-M25	-	H16A-TG-M25	-	H16A-AG	-	H16A-SGR-M25	-
Size 6	M25	H16B-TS-R0-M25	H16B-TS-M25	H16B-TG-R0-M25	H16B-TG-M25	H16B-AG-LB	H16B-AG	H16B-SGR-LB-M25	H16B-SGR-M25
Size 7	M32	-	H32A-TS-M32	-	H32A-TG-M32	-	H32A-AG	-	H32A-SGR-M32
Size 8	M32	H24B-TS-R0-M32	H24B-TS-M32	H24B-TG-R0-M32	H24B-TG-M32	H24B-AG-LB	H24B-AG	H24B-SGR-LB-M32	H24B-SGR-M32
Size 10	M32	H32B-TS-R0-M32	H32B-TS-M32	H32B-TG-R0-M32	H32B-TG-M32	H32B-AG-LB	H32B-AG	H32B-SGR-LB-M32	H32B-SRG-M32
Size 12	M40	H48B-TS-R0-M40	-	H48B-TG-R0-M40	-	H48B-AG-LB	-	H48B-SGR-LB-M40	-
熱流道系統 Hot Runner									
外殼規格	入線孔徑	單扣 1 Lever	雙扣 2 Levers	單扣 1 Lever	雙扣 2 Levers	單扣 1 Lever	雙扣 2 Levers	單扣 1 Lever	雙扣 2 Levers
Size 6	M25	-	H16B-TSB-M25	-	H16B-TGB-M25	-	H16B-AD-B0	-	H16B-SDR-B0-M25
Size 8	M32	-	H24B-TSB-M32	-	H24B-TGB-M32	-	H24B-AD-B0	-	H24B-SDR-B0-M32



HM Series
Modular Type

HM Series							
接插體 Insert	公 (M)	HM-004-M	HM-006-M	HM-008-M	HM-012-M	HM-017-M	HM-025-M
	母 (F)	HM-004-F	HM-006-F	HM-008-F	HM-012-F	HM-017-F	HM-025-F
冷壓針 Crimp Terminal	公 (M)	CMM-1.5~6.0	CEM-0.5~6.0	CEM-0.5~4.0	CDM-0.5~2.5	CDM-0.5~2.5	CAM-13 DAM-13
	母 (F)	CMF-1.5~6.0	CEF-0.5~6.0	CEF-0.5~4.0	CDF-0.5~2.5	CDF-0.5~2.5	CAF-13 DAF-13

模塊數 Modules				
框架/外殼 Frames/Housings				
框架 Frames	H6B-T2-M (A-B) H6B-T2-F (a-b)	H10B-T3-M (A-C) H10B-T3-F (a-c)	H16B-T4-M (A-D) H16B-T4-F (a-d)	H24B-T6-M (A-F) H24B-T6-F (a-f)
插頭外殼 Hoods	H6B-TG-M20	H10B-TG-M25	H16B-TG-M25	H24B-TGH-M32
底座外殼 Housings	H6B-AG	H10B-AG	H16B-AG	H24B-AG

XCG Series 電纜接頭 Cable Glands IP68					
Thread Cable Dia. mm		公制 Metric	歐規 PG	公制 Metric	歐規 PG
Φ 4~8		M16-08G-P	PG11-08G-P	M16-08-M	PG11-08-M
Φ 6~12		M20-12G-P	PG13.5-12G-P	M20-12-M	PG13.5-12-M
Φ 13~18		M25-18G-P	PG21-18G-P	M25-18-M	PG21-18-M
Φ 18~25		M32-25G-P	PG29-25G-P	M32-25-M	PG29-25-M
Φ 22~32		M40-32G-P	PG36-32G-P	M40-32-M	PG36-32-M



XT-AF8-UH2-5
26~12AWG
0.13~3.3 mm²



XT-AFM8-SK2/2
32~20AWG
0.032~0.5 mm²