

Camera Link 機器視覺連接綫

Camera Link Cables

特點 Features

- 兼容Camera Link V2.0 標準規範
- TPU 或 PA 工程塑料注塑成型
- 耐油耐彎曲超柔屏蔽電纜，彎曲壽命500萬次
- 採用UL 認證材料，符合 CE 和 RoHS 規範
- Compatible with Camera Link V2.0 standard
- Durable TPU or PA overmolding for industrial applications
- Flexible oil-resistant shielded cable for 5 million bending cycles
- UL approval materials, CE and RoHS compliant

訂購編號 Ordering Information

XMV-CL-M 1-H U-VS 3

① ② ③ ④ ⑤ ⑥ ⑦

① 接口標準 Interface Standard

- CL** Camera Link
- PoCL** Power over Camera Link
- PoCLL** Power over Camera Link-Lite

②、④ 連接器型式 Connector Type

- M** MDR MALE 26P
- H** HDR MALE 26P
- HS** HDR MALE 14P(POCL Lite)

③、⑤ 注塑型式 Overmold Type

- 1** 直型 Straight
- U** 上彎型 Up Angle
- D** 下彎型 Down Angle
- L** 左彎型 Left Angle
- R** 右彎型 Right Angle
- UE** 上彎長型 Extended Up Angle
- DE** 下彎長型 Extended Down Angle
- LE** 左彎長型 Extended Left Angle
- RE** 右彎長型 Extended Right Angle

⑥ 電纜類型 Cable Type

- VS** 超柔電纜 Flexible PVC Cable Black
- US** 耐彎曲電纜 Durable PUR Cable Green
- LS** 低烟無鹵電纜 LSZH Cable Black

⑦ 綫長(米) Cable Length(m) **1~10**

連接器型式 Connector Type Options



GigE 機器視覺連接綫

GigE Vision Cables

特點 Features

- 兼容GigE V2.0 標準規範
- TPU 或 PA 工程塑料注塑成型
- 耐油耐彎曲超柔 Cat 6a 電纜，彎曲壽命500萬次
- 采用UL 認證材料，符合 CE 和 RoHS 規範
- Compatible with GigE V2.0 standard
- Durable TPU or PA overmolding for industrial applications
- Flexible oil-resistant Cat 6a cable for 5 million bending cycles
- UL approval materials, CE and RoHS compliant

訂購編號 Ordering Information

XMV-GE-H 1-RS U-VS 3

① ② ③ ④ ⑤ ⑥ ⑦

① 接口標準 Interface Standard

GE GigE Vision

②、④ 連接器型式 Connector Type

- H** 直型插頭 Horizontal RJ45 Plug
- HS** 直型螺絲插頭 Horizontal RJ45 Plug With Screw
- VS** 垂直螺絲插頭 Vertical RJ45 Plug With Screw
- RS** 彎型螺絲插頭 Angled RJ45 Plug With Screw
- MX** 圓型插頭 M12 X-Code 8P Plug

③、⑤ 注塑型式 Overmold Type

- 1** 直型 Straight
- U** 上彎型 Up Angle
- D** 下彎型 Down Angle
- L** 左彎型 Left Angle
- R** 右彎型 Right Angle

⑥ 電纜類型 Cable Type

- VS** 超柔電纜 Flexible Cat 6a PVC Cable Black
- US** 耐彎曲電纜 Durable Cat 6a PUR Cable Green
- LS** 低煙無鹵電纜 LSZH Cat 6a Cable Black

⑦ 綫長(米) Cable Length(m) **1~20**

連接器型式 Connector Type Options

